www.bxb.tw

Your Best Partner!
with Ultimate Choice

FCS 6051 Main Control Unit
(W/ Voting, W/LCD)



- Has three (3) chain outputs for daisy connection, each link can be linked up to 25 units
- Can control up to10 chairman units & 500 delegate units by extension power supply
- Has 4x20 digit LCD monitor display, the configurations can be set up and displayed from it
- Multi-Conferencing Operating Modes:
  - NORMAL/OVERRIDE/CHAIRMAN
  - FIFO: 1. Delegates have the ability to open their own mics 2. When the maximum open mics is reached, mics will go into request-to-speak que
  - OPEN-MIC: Numbers of Microphone push to talk simultaneously is up to 1-30
  - VOICE (Auto-MIC Shut-Off): 10-99 seconds without speaking, microphone will be automatically shut-off
- System Auto-Test functions when power on. When failed connection, the Red ring of light is flashing
- Main control unit and Chairman Unit controls all delegate mice activation and has the alarm sound when delegate-off
- Provides RS-232 interface is supported with Creston or AMX wired or wireless touch screens
- Built-in Video Control Management Interface
  - Three (3) Phased Images Auto-Tracing Functionality: BUTTON/VOICE/PRESET
- Has LED Volume Indicators
- Built-in sound-emission circuit to prevent echo and noise
- Synchronized with BXB Authorized Conference Management Software
- Digital Volume Adjustment
- Built-in Voting Functionality

TECHNICAL SPECIFICATIONS	
Frequency response	100HZ~16KHZ
LINE IN：	-4dB~+6dB≧10KΩ（Balanced）
LINE OUT：	-4dB~+12dB≧200Ω（Balanced）
Sensitivity：	-60dB
T.H.D.：	≦0.5%
S/N Ratio：	≧90dB
Conference microphone connection：	D type 9P express port x 3 sets
MIC (XLR) Input	1 set x 600Ω/6mV/-22dB (Digital Control)
Line (XLR) Input	1 set x 20KΩ/300mV/-10dB(Digital Control)
Volume Indicators	5 LEDs
Power	AC110/220，50/60Hz，Power LED light
Width x Height x Depth	431 x 94 x 311 mm
Weight	8 (kg)

*The appearance and specifications of all item are subject to change without notice

6F-1, No.288-5, Shin Ya Road, Chien Chen District, Kaohsiung, Taiwan, R.O.C. 80673
TEL：+886(7)970-3838 FAX：+886(7) 970-3883 Email: bxb@bxb.tw http://www.bxb.tw
BXB ELECTRONICS CO., LTD. All rights reserved 121508