FCS-6321N/6322N

Flush-mounted Chairman/Delegate Unit



- Extruded aluminum panel design that can be easily mixed with conferencing table.
- Equipped with DSP chip, AGC, and sensitivity adjustment for each microphone.
- 2 x Ø3.5mm audio out connectors: one for headphone (volume adjustable); one for connecting with recording equipment.
- There's no limitation of chairman unit's quantity. You can also randomly put the chairman unit with any sequence.
- Microphone auto-off as 10-99 seconds after the speaker finish speaking.
- Goosenck microphone with LED indicator light. Length offered: 32/43/48/56 (cm).
- Adaptable with different meeting environments.

Specifications

Frequency Response	100HZ~16KHZ
Sensitivity	≧-50dB
T.H.D	≦0.1%
S/N Ratio	≧70dB
AGC	-45 ~ 0dB
Communication Port	RJ-45 x 2 , RJ-11 x 1
Earphone Port	3.5Ø Stereo x 1
Recording Port	3.5Ø Stereo x 1

Unit Dimension (WHD)	170 x 43 × 82 (mm)
Weight	346g (not including gooseneck mic)
Material	Galvanized steel
Mounting Hole (WHD)	142 x 33 x 132 (mm)
Voltage	DC 12V~18V (supplied by FCS-6350 MCU)

BXB
ADD 6F-1, No.288-5, Xinya Rd., Qianzhen Dist., Kaohsiung City 80673, Taiwan
TEL +886 7 9703838
FAX +886 7 9703883
MAIL bxb@bxb.tw
WEB www.bxbsystem.com