# FCS-6321S / FCS-6322S

## Flush-mounted Chairman/Delegate Unit



- Extruded aluminum panel design that can be easily mixed with conferencing table.
- Equipped with DSP chip, AGC, and sensitivity adjustment for each microphone.
- 2 x Ø3.5mm audio out connectors: one for headphone (volume adjustable); one for connecting with recording equipment.
- There's no limitation of chairman unit's quantity. You can also randomly put the chairman unit with any sequence.
- Microphone auto-off as 10-99 seconds after the speaker finish speaking.
- Goosenck microphone with LED indicator light. Length offered: 32/43/48/56 (cm).
- Adaptable with different meeting environments.

## Specifications

| | |
|---|---|
| **Frequency Response** | 100HZ~16KHZ |
| **Sensitivity** | ≧-50dB |
| **T.H.D** | ≦0.1% |
| **S/N Ratio** | ≧70dB |
| **AGC** | -45 ~ 0dB |
| **Communication Port** | RJ-45 x 2 , RJ-12 x 1 |
| **Earphone Port** | 3.5Ø Stereo x 1 |
| **Recording Port** | 3.5Ø Stereo x 1 |

| | |
|---|---|
| **Unit Dimension (WHD)** | 170 x 43 × 82 (mm) |
| **Weight** | 346g (not including gooseneck mic) |
| **Material** | Galvanized steel |
| **Mounting Hole (WHD)** | 142 x 33 x 132 (mm) |
| **Voltage** | DC 12V~18V (supplied by FCS-6350 MCU) |

BXB
ADD 6F-1, No.288-5, Xinya Rd., Qianzhen Dist., Kaohsiung City 806604, Taiwan
TEL +886 7 9703838
FAX +886 7 9703883
MAIL bxb@bxb.tw
WEB www.bxbsystem.com