PAB-5400

Power Amplifier 220V



Product Features

- Protection Switch: The front panel is equipped with power and overload indicators, featuring AC and DC automatic trip switches.
- Overheat Protection: When the internal temperature exceeds 85°C, the fault indicator will remain lit and the unit will automatically shut down.
- Volume Control: Selectable master or sub-unit output. The master unit features adjustable output volume control and dual-row LED indicators.
- Parallel Expansion: Constant voltage outputs can be connected in parallel to increase the total output power.
- Cooling System: Built-in large cooling fan with automatic temperature control.
- Power Trigger: Equipped with a trigger contact for automatic power-on.
- Safety Certifications: Certified under Taiwan's BSMI standards (CNS 15598-1, CNS 15936, CNS 15663), ensuring comprehensive compliance
- with electrical safety, electromagnetic interference (EMI), and restricted substance regulations.

Specifications

Product Specifications

Output power	RMS 400W / MAX 550W
Frequency response	50Hz ~ 20kHz
Distortion rate	≤ 1% under full load (1KHZ)
S / N ratio	≧ 80dB

Appearance	19-inch standard cabinet (4U)
Weight	About 20kg
Speaker output	100V / 70V / 8Ω
Input / Output	With signal input / output terminal (PHONE JACK socket two groups)
Power	AC 100V ~ 120V or 220V ~ 240V (50 / 60HZ) / DC: 24V

BXB

ADD 6F-1, No.288-5, Xinya Rd., Qianzhen Dist., Kaohsiung City 80673, Taiwan

TEL +886 7 9703838

FAX +886 7 9703883

MAIL bxb@bxb.tw

WEB www.bxbsystem.com