WMP-60D

Remote Decoder



Product Features

- Uses **DIP** switches to configure Zone IDs (address codes for classrooms, offices, and other areas).
- Features a tri-color **LED** status indicator to display modes: General Broadcasting, Two-way Intercom, and **Call-back**signal activity.
- Includes a failsafe mechanism: if the **Decoder** encounters a line fault or power failure, it automatically bypasses to the analog **PA** signal to ensure uninterrupted broadcasting.
- Equipped with a trigger input for a **Call-back** button. Upon activation, the corresponding zone indicator flashes Orange on the main unit. An emergency alert tone can be pre-configured via the **Graphical Control Software** to notify staff for immediate response.
- Features an **NC** (Normally Closed) trigger input for connecting security sensors. Upon detection, the zone indicator flashes Red on the main unit. An intrusion alarm tone can be pre-configured via the **Graphical Control Software** to alert staff.
- Provides a **DC-12V** output to trigger a local **Strobe Siren**. When a **Call-back** signal is activated, the local alarm engages to deter intruders. This alarm can be reset remotely from the decoder, the main controller, or other control points.



WMP-60D Remote Decoder

Product Specifications

Output Load	100V：1A
Broadcast Audio Input	100V/COM x 1 Set
Broadcast Audio Output	100V/COM x 1 Set
LED Status Indicator	Tri-color LED (Green, Orange, Red)

Multi-function Control Interface	8 Set
Trigger Input (N.O.)	1 Set
Trigger Input (N.C.)	1 Set
12V Trigger Output	1 Set

Dimensions (H x W x D)	40 x 90 x 180 mm
Weight	0.18 kg
Housing Material	ABS

ADD 6F-1, No.288-5, Xinya Rd., Qianzhen Dist., Kaohsiung City 806604, Taiwan
TEL +886 7 9703838
FAX +886 7 9703883
MAIL bxb@bxb.tw
WEB www.bxbsystem.com

WMP-60D-C

Remote Decoder + Intercom Modual



Product Features

- Uses **DIP** switches to configure Zone IDs (address codes for classrooms, offices, and other areas).
- Features a tri-color **LED** status indicator to display modes: General Broadcasting, Two-way Intercom, and **Call-back**signal activity.
- Includes a failsafe mechanism: if the **Decoder** encounters a line fault or power failure, it automatically bypasses to the analog **PA** signal to ensure uninterrupted broadcasting.
- Equipped with a trigger input for a **Call-back** button. Upon activation, the corresponding zone indicator flashes Orange on the main unit. An emergency alert tone can be pre-configured via the **Graphical Control Software** to notify staff for immediate response.
- Features an **NC** (Normally Closed) trigger input for connecting security sensors. Upon detection, the zone indicator flashes Red on the main unit. An intrusion alarm tone can be pre-configured via the **Graphical Control Software** to alert staff.
- Provides a **DC-12V** output to trigger a local **Strobe Siren**. When a **Call-back** signal is activated, the local alarm engages to deter intruders. This alarm can be reset remotely from the decoder, the main controller, or other control points.
- Built-in **omni-directional microphone** captures clear audio during Intercom mode and transmits it back to the main unit.

WMP-60D-C Remote Decoder + Intercom Modual

Product Specifications

Output Load	100V：1A
Broadcast Audio Input	100V/COM x 1 Set
Broadcast Audio Output	100V/COM x 1 Set
Intercom Audio Input	Omnidirectional Microphone x 1 Set
LED Status Indicator	Tri-color LED (Green, Orange, Red)

Multi-function Control Interface	8 Set
Trigger Input (N.O.)	1 Set
Trigger Input (N.C.)	1 Set
12V Trigger Output	1 Set

Dimensions (H x W x D)	40 x 90 x 180 mm
Weight	0.2 kg
Housing Material	ABS

BXB
ADD 6F-1, No.288-5, Xinya Rd., Qianzhen Dist., Kaohsiung City 806604, Taiwan
TEL +886 7 9703838
FAX +886 7 9703883
MAIL bxb@bxb.tw
WEB www.bxbsystem.com

WMP-61D

Remote Decoder



Product Features

- Uses **DIP** switches to configure Zone IDs (address codes for classrooms, offices, and other areas).
- Features a tri-color **LED** status indicator to display modes: General Broadcasting, Two-way Intercom, and **Call-back**signal activity.
- Includes a failsafe mechanism: if the **Decoder** encounters a line fault or power failure, it automatically bypasses to the analog **PA** signal to ensure uninterrupted broadcasting.
- Equipped with a trigger input for a **Call-back** button. Upon activation, the corresponding zone indicator flashes Orange on the main unit. An emergency alert tone can be pre-configured via the **Graphical Control Software** to notify staff for immediate response.
- Features an **NC** (Normally Closed) trigger input for connecting security sensors. Upon detection, the zone indicator flashes Red on the main unit. An intrusion alarm tone can be pre-configured via the **Graphical Control Software** to alert staff.
- Provides a **DC-12V** output to trigger a local **Strobe Siren**. When a **Call-back** signal is activated, the local alarm engages to deter intruders. This alarm can be reset remotely from the decoder, the main controller, or other control points.
- Rated for a **10A output load**, capable of driving a **100V PA line** with a maximum speaker power capacity of **1000W**.



WMP-61D Remote Decoder

Product Specifications

Output Load	100V：10A
Broadcast Audio Input	100V/COM x 1 Set
Broadcast Audio Output	100V/COM x 1 Set
LED Status Indicator	Tri-color LED (Green, Orange, Red)

Multi-function Control Interface	8 Set
N.O. Input Trigger	1 Set
N.C. Input Trigger	1 Set
12V Trigger Output	1 Set

Dimensions (H x W x D)	40 x 90 x 180 mm
Weight	0.18 kg
Housing Material	ABS

BXB
ADD 6F-1, No.288-5, Xinya Rd., Qianzhen Dist., Kaohsiung City 806604, Taiwan
TEL +886 7 9703838
FAX +886 7 9703883
MAIL bxb@bxb.tw
WEB www.bxbsystem.com

WMP-60E

Remote Decoder + Auto On/Off



Product Features

- Uses **DIP** switches to configure Zone IDs (address codes for classrooms, offices, and other areas).
- Features a tri-color **LED** status indicator to display modes: General Broadcasting, Two-way Intercom, and **Call-back**signal activity.
- Includes a failsafe mechanism: if the **Decoder** encounters a line fault or power failure, it automatically bypasses to the analog **PA** signal to ensure uninterrupted broadcasting.
- Equipped with a trigger input for a **Call-back** button. Upon activation, the corresponding zone indicator flashes Orange on the main unit. An emergency alert tone can be pre-configured via the **Graphical Control Software** to notify staff for immediate response.
- Features an **NC** (Normally Closed) trigger input for connecting security sensors. Upon detection, the zone indicator flashes Red on the main unit. An intrusion alarm tone can be pre-configured via the **Graphical Control Software** to alert staff.
- Provides a **DC-12V** output to trigger a local **Strobe Siren**. When a **Call-back** signal is activated, the local alarm engages to deter intruders. This alarm can be reset remotely from the decoder, the main controller, or other control points.
- Features a **6.3 mm microphone output** for connecting to external amplifiers or other PA equipment.
- Includes an **NC** (Normally Closed) output contact to automatically activate amplifiers or power controllers during broadcasting.



WMP-60E Remote Decoder + Auto On/Off

Product Specifications

Broadcast Audio Input	100V/COM x 1 Set
Broadcast Audio Output	Φ6.3 mm Microphone Audio Source x 1 Set
LED Status Indicator	Tri-color LED (Green, Orange, Red)

Multi-function Control Interface	8 Set
N.O. Input Trigger	1 Set
N.C. Input Trigger	1 Set
N.O. Output Trigger	1 Set
12V Trigger Output	1 Set

Dimensions (H x W x D)	40 x 90 x 180 mm
Weight	0.24 kg
Housing Material	ABS

BXB
ADD 6F-1, No.288-5, Xinya Rd., Qianzhen Dist., Kaohsiung City 806604, Taiwan
TEL +886 7 9703838
FAX +886 7 9703883
MAIL bxb@bxb.tw
WEB www.bxbsystem.com

WMP-60F

Remote Decoder



Product Features

- Uses **DIP** switches to configure Zone IDs (address codes for classrooms, offices, and other areas).
- Features a tri-color **LED** status indicator to display modes: General Broadcasting, Two-way Intercom, and **Call-back**signal activity.
- Includes a failsafe mechanism: if the **Decoder** encounters a line fault or power failure, it automatically bypasses to the analog **PA** signal to ensure uninterrupted broadcasting.
- Equipped with a trigger input for a **Call-back** button. Upon activation, the corresponding zone indicator flashes Orange on the main unit. An emergency alert tone can be pre-configured via the **Graphical Control Software** to notify staff for immediate response.
- Features an **NC** (Normally Closed) trigger input for connecting security sensors. Upon detection, the zone indicator flashes Red on the main unit. An intrusion alarm tone can be pre-configured via the **Graphical Control Software** to alert staff.
- Provides a **DC-12V** output to trigger a local **Strobe Siren**. When a **Call-back** signal is activated, the local alarm engages to deter intruders. This alarm can be reset remotely from the decoder, the main controller, or other control points.
- Includes a **3.5 mm audio output** compatible with instructional amplification systems, such as the **ADM-1000 DECT Digital Wireless Microphone**.



WMP-60F Remote Decoder

Product Specifications

Broadcast Audio Input	100V/COM x 1 組
Broadcast Audio Output	Φ3.5 mm Microphone Audio Source x 1 組
LED Status Indicator	Tri-color LED (Green, Orange, Red)

Multi-function Control Interface	8 Set
Trigger Input (N.O.)	1 Set
Trigger Input (N.C.)	1 Set
12V Trigger Output	1 Set

Dimensions (H x W x D)	40 x 90 x 180 mm
Weight	0.25 kg
Housing Material	ABS

BXB
ADD 6F-1, No.288-5, Xinya Rd., Qianzhen Dist., Kaohsiung City 806604, Taiwan
TEL +886 7 9703838
FAX +886 7 9703883
MAIL bxb@bxb.tw
WEB www.bxbsystem.com