UFO-2021/2022

Flush-mounted Chairman/Delegate Unit



- Extruded aluminum panel design that can be easily mixed with conferencing table.
- Equipped with DSP chip and sensitivity adjustment for each microphone.
- 2 x Ø3.5mm audio out connectors: one for headphone (volume adjustable); one for connecting with recording equipment.
- There's no limitation of chairman unit's quantity. The chairman unit can be placed in any sequence.
- The panel is equipped with red / green / orange LED indicator light to represent different operation modes.
- Chairman unit has the priority to speak and control: operates permanent OFF and temporary OFF. A tone will be generated to raise attendee's attention.
- The head of the gooseneck microphone features a red LED light ring to indicate active use. It is available in multiple lengths (32, 43, 48, and 56 cm), with a choice of either a flexible or rigid tube. Furthermore, a dual-gooseneck model, the WM-70 B2HT, is also offered to suit various environmental requirements.

Specifications

Frequency Response	100HZ~16KHZ
Sensitivity	≧-50dB
T.H.D	≦0.1%
S/N Ratio	≧70dB
AGC	-45 ~ 0dB
Communication Port	RJ-45 x 2 , RJ-11 x 1
Earphone Port	3.5Ø Stereo x 1
Recording Port	3.5Ø Stereo x 1

Unit Dimension (WHD)	170 x 43 × 82 (mm)
Weight	346g (not including gooseneck mic)
Material	Galvanized steel
Mounting Hole (WHD)	142 x 33 x 132 (mm)
Voltage	DC 12V~18V (supplied by UFO-2050 MCU)
Model Name of Gooseneck Mic	WM-43/48/56 B1HT; WM-70 B2HT

BXB
ADD 6F-1, No.288-5, Xinya Rd., Qianzhen Dist., Kaohsiung City 806604, Taiwan
TEL +886 7 9703838
FAX +886 7 9703883
MAIL bxb@bxb.tw
WEB www.bxbsystem.com