FCS-6331S

Flush-mounted Delegate Unit



Product Features

- Digital DSP Technology: AGC and independent adjustment of microphone sensitivity ensure clear and full voice reproduction.
- Easy Operation: Equipped with an ON/OFF speaking button and LED tri-color indicator lights for instant recognition of three speaking modes (Request to Speak / FIFO Mode / Override Mode).
- Real-time Monitoring: Features an output volume control knob and built-in high-quality speaker for real-time monitoring of spoken content.
- Flexible Connectivity: Two RJ45 ports support hot-pluging, making the operation simple without the need for complex settings.
- Easy Recording: Built-in Ø3.5mm stereo jack for easy connection to recording devices, facilitating meeting recording.
- Image Tracking: Connects to the conference MCU and BXB VT-725 Image Tracking Controller to set PTZ camera tracking points.
- Versatile Installation: Can be placed on a desktop or securely fixed to the armrest, suitable for various occasions.
- Compatible with WM-H1 Handheld Mic for optimal meeting speaking performance.

WM-H1

Hand-held Microphone



- Connect to the BXB FCS-6331S unit for optimal speaking quality.
- Digital Encoding: Say goodbye to traditional DIP switch, mic ID and attendee's role can be changed from the conference MCU and control software.
- Unique Cardioid Design: Precisely captures human voices while simultaneously covering background noise, ensuring clear speech.
- Professional-grade Recording: Built-in windscreen and low-noise interference feature resist environmental noise and explosive sounds, maintaining pure audio quality.
- Sleek Appearance: Equipped with a ON/OFF speaking key. The red light ring illuminates when speaking, indicating the status at a glance.
- Easy to Use: Features 2.2-meter and 4.5-meter coiled spring cable, making installation convenient and keeping everything tidy.

Specifications（WM-H1 + FCS-6331S）

Frequency Response	100HZ~16KHZ
Sensitivity	≧-50dB
T.H.D	≦0.1%
S/N ratio	≧70dB
AGC	-45 ~ 0dB
Voltage	DC 24V

FCS-6331S Connection Interface	RJ-45 x 2
FCS-6331S Indicator Lights	red / green / orange
Headphone/Recording Jack	3.5Ø stereo
Dimensions (WHD)	170 x 82 x 43 mm (FCS-6331S)
Weight	346g (FCS-6331S)

BXB
ADD 6F-1, No.288-5, Xinya Rd., Qianzhen Dist., Kaohsiung City 806604, Taiwan
TEL +886 7 9703838
FAX +886 7 9703883
MAIL bxb@bxb.tw
WEB www.bxbsystem.com