# FCS-6323N / 6324N

## Flush-mounted Chairman/Delegate Unit



- Aluminum alloy metal panel, with rounded and simple line design, allowing the panel to seamlessly integrate into the desktop.
- Two sets of Ø3.5mm audio output jacks: one set can connect headphones with volume adjustment, and the other allows to plug in recording devices for conference recording.
- Adopts the globally recognized Cat-5e network cable.
- There is no limit to the number of chairman units in the system, and they can be placed at any position in the loop.
- Microphone unit can be set to auto-off 10-99 seconds after the end of the speech.
- Equipped with 5 LED voting buttons that execute Attendance, Agree(+), Disagree(-), Abstain(0) (voting function) / Numbers: 1-5 or A-B (multiple-choice voting).

### Hardware Specifications

| | |
|---|---|
| Frequency Response | 100HZ~16KHZ |
| Sensitivity | ≧-50dB |
| Total Harmonic Distortion | ≦0.1% |
| S/N Ratio | ≧70dB |
| AGC | -45 ~ 0dB |
| Communication Interface | RJ-45 x 2, RJ-11 x 1 |
| Headphone Interface | 3.5Ø Stereo x 1 |
| Recording Interface | 3.5Ø Stereo x 1 |

### Physical Dimensions

| | |
|---|---|
| Dimensions (H x W x D) | 43 x 320 x 75 (mm) |
| Weight | 800g (excluding gooseneck microphone) |
| Material | Galvanized steel plate |

### Power Supply

| | |
|---|---|
| Voltage | DC 12V~18V |

BXB
ADD 6F-1, No.288-5, Xinya Rd., Qianzhen Dist., Kaohsiung City 806604, Taiwan
TEL +886 7 9703838
FAX +886 7 9703883
MAIL bxb@bxb.tw
WEB www.bxbsystem.com