FCS-6323S / 6324S

Flush-mounted Chairman/Delegate Unit



- Aluminum alloy metal panel, with rounded and simple line design, allowing the panel to seamlessly integrate into the desktop.
- Two sets of Ø3.5mm audio output jacks: one set can connect headphones with volume adjustment, and the other allows to plug in recording devices for conference recording.
- Adopts the globally recognized Cat-5e network cable.
- There is no limit to the number of chairman units in the system, and they can be placed at any position in the loop.
- Microphone unit can be set to auto-off 10-99 seconds after the end of the speech.
- Equipped with 5 LED voting buttons that execute Attendance, Agree(+), Disagree(-), Abstain(0) (voting function) / Numbers: 1-5 or A-B (multiple-choice voting).

Hardware Specifications

Frequency Response	100HZ~16KHZ
Sensitivity	≧-50dB
Total Harmonic Distortion	≦0.1%
S/N Ratio	≧70dB
AGC	-45 ~ 0dB
Communication Interface	RJ-45 x 2, RJ-11 x 1
Headphone Interface	3.5Ø Stereo x 1
Recording Interface	3.5Ø Stereo x 1

Physical Dimensions

Dimensions (W x H x D)	320 x 82 x 43mm
Weight	800g (excluding gooseneck microphone)
Material	Galvanized steel plate

Power Supply

Voltage	DC 12V~18V

BXB
ADD 6F-1, No.288-5, Xinya Rd., Qianzhen Dist., Kaohsiung City 806604, Taiwan
TEL +886 7 9703838
FAX +886 7 9703883
MAIL bxb@bxb.tw
WEB www.bxbsystem.com