
ICP-5152

Programmed Media Gateway



- Collect and manage all the equipment via network exchange and execute audio/video matrix play.
- Connect with ICP-5180 Central Control Unit for playing 1080p video with digital IP packet transmission. The transmission distance can reach 100M and it supports connecting with switches for distance extension.
- Provide 24 sets of 10/100/1000M bps LAN ports and 4 sets of Combo optical fiber modules; the connection can reach 10 miles.
- Work with the graphical control software to auto-recognize the connected receivers (IP decoders), transmitters (various converters), serial ports (network switches), and PCs.
- It can manage over 255 sets of receivers/transmitters.
- Equipped with network traffic control: set the bandwidth limit to each port and user's IP.
- Plug-and-play without installing any software or driver.

Product Specifications

Port Density	10 / 100 / 1000 Mbps RJ45 ports x 24, MDI / MDI-X SFP 100 / 100 Mbps ports x 4 DB9 Console port x 1
Button	Reset to default setting x 1
Ethernet Standard	IEEE 802.3, 802.3u, 802.3ab
Flow Control	IEEE 802.3x
Jumbo Frame	1518~10K Bytes

IGMP Snooping	v2 / v3
Layer 2 Switching	QoS, CoS, DSCP, Weighted Round-Robing (WRR), SP, IP Precedence
Link Aggregation	8 groups with static & LACP types
Dimensions (WHD)	441 x 131 x 44 mm
Weight	2.2kg

BXB
ADD 6F-1, No.288-5, Xinya Rd., Qianzhen Dist., Kaohsiung City 80673, Taiwan
TEL +886 7 9703838
FAX +886 7 9703883
MAIL bxb@bxb.tw
WEB www.bxbsystem.com