WS-817 Series

Wall Speaker



Product Features

- Speaker Unit: Coaxial two-way, 6.5-inch low-frequency, 2-inch high-frequency x2. Two speaker units are installed in the same speaker box, providing better sound quality and increased sound pressure.
- The amplifier module can be installed inside the speaker box, combined with the preamplifier panel, it can be used as a teaching amplifier set.
- The remote control decoder can be installed inside the speaker box, compatible with the computer broadcasting host, for digital zoning broadcasting/intercom use.
- Integrated architectural-style design, silver-gray color scheme, suitable for various decorative styles.
- The speaker enclosure is made of fire-resistant ABS material, providing excellent fire resistance.

BXB
ADD 6F-1, No.288-5, Xinya Rd., Qianzhen Dist., Kaohsiung City 806604, Taiwan
TEL +886 7 9703838
FAX +886 7 9703883
MAIL bxb@bxb.tw
WEB www.bxbsystem.com

Product Specifications				
Model No	**WS-817L**	**WS-817TL**	**WS-817**	**WS-817T**
Rated Input	35W		45W	
S.P.L	94 ~ 107dB	94 ~ 105dB	90 ~ 103dB	90 ~ 100dB
Frequency response	80 - 15KHz		60 - 20KHz	
Speaker unit	6.5" × 2		Coaxial Two Way (Low6.5" / High2") ×2	
Input impedance	4Ω	100V LINE 3W-3.3KΩ 6W-1.7KΩ 10W-1KΩ	4Ω	100V LINE 3W-3.3KΩ 6W-1.7KΩ 10W-1KΩ
Mounting Type	Wall Mounted			
Dimension (L x W x H)	350 x 250 x 160(mm)			
Weight	2.6 kg	2.8 kg	3.0 kg	3.2 kg
Box Material	ABS			

BXB
ADD 6F-1, No.288-5, Xinya Rd., Qianzhen Dist., Kaohsiung City 806604, Taiwan
TEL +886 7 9703838
FAX +886 7 9703883
MAIL bxb@bxb.tw
WEB www.bxbsystem.com