UFO-2011 / UFO-2012

Table-top Chairman / Delegate Unit



- Streamlined look and concealed speaking push-button makes the unit's more elegant and flowing.
- Equipped with DSP chip and sensitivity adjustment for enhancing the audio quality.
- Chairman unit has the highest priority to speak and control delegate unit's speaking status.
- The electric gooseneck microphone is equipped with a LED indicator ring and able to avoid the interference of electromagnetic from 3G and 4G cell phones.
- Lengths of pluggable gooseneck microphone: Available in various lengths, including 32/43/48/56 cm, with soft and hard tube options. A WM-70 B2HT dual gooseneck microphone is also available for use depending on the on-site environment.

Specifications

Voltage	DC 12~24V (supplied by MCU)	**S/N Ratio**	≧ 70dB	**Dimension (WHD)**	125 x 165 x 45mm
Connector	RJ45 x 2	**Sensitivity**	≧ -50db	**Weight**	610g
T.H.D	≦ 0.1%	**Gooseneck Mic Length**	43/48/56/70cm	**Color (Unit Cover)**	Black / silver / bronze / champagne gold / iron-grey silver
Frequency Response	100Hz~16KHz				

BXB
ADD 6F-1, No.288-5, Xinya Rd., Qianzhen Dist., Kaohsiung City 80673, Taiwan
TEL +886 7 9703838
FAX +886 7 9703883
MAIL bxb@bxb.tw
WEB www.bxbsystem.com