# WM-43/48/56 B1HT、WM-70 B2HT

## Gooseneck Microphone



## Product Features

- Features a hot-swappable DIN connector for seamless integration with EDC-2000, UFO-2000, and FCS-6300 series desktop and flush-mounted units.
- An illuminated red LED ring at the microphone tip indicates active status.
- Available in 43, 48, 56, and 70 cm lengths. The 70 cm version features a dual-flex gooseneck for versatile positioning to suit any environment.
- Engineered to resist interference from mobile phones and electromagnetic waves. It effectively shields against noise from 3G and 4G devices transmitting or receiving within 10 cm of the microphone capsule.
- The gooseneck is constructed from a noise-dampening material and incorporates an acoustic foam windscreen, preventing handling noise from adjustments. It holds its position firmly and remains silent even with prolonged use.

### Product Specifications

| | |
|---|---|
| Frequency Response | 65 ~ 20000 Hz |
| Output Impedance | 680Ω (1Khz) |
| Sensitivity | -47±3dB (0dB=1V/Pa,at 1KHz) |
| Maximum SPL | 100dB (THD<5%, at 1KHz) |
| S/N Ratio | 55dB |

### Product Specifications

| | |
|---|---|
| Cartridge Type | Electret |
| Directional Pattern | Uni-directional |
| Connector | DIN |
| Polar Pattern | Cardioid |
| Operating Voltage | 1 ~ 5 V |

### Product Specifications

| | |
|---|---|
| Length | 430 / 480 / 560 mm |
| Weight | 82 / 87 / 95.5 g |
| Storage Temperature | -25°C ~ +70°C |
| Operating Temperature | -20°C ~ +60°C |

BXB
ADD 6F-1, No.288-5, Xinya Rd., Qianzhen Dist., Kaohsiung City 806604, Taiwan
TEL +886 7 9703838
FAX +886 7 9703883
MAIL bxb@bxb.tw
WEB www.bxbsystem.com