# FCS-6325-43

## Conference Lifting Microphone



**Store the Microphone Under the Table**

**Give Back the Original Table Space to You**

## Product Features

- Once finish using, the microphone can be lifted down and hidden under the table. The cover would be automatically closed. Keep the table neat. No exposed cable required.
- One button for electrical lifting and descending. Fast and stable operation without noise and shake.
- During the meeting, the microphone can be lifted individually or concurrently.
- Via central control system, you can lift single, multiple, or all microphones based on the demands.
- Supports RS-485 protocol for remote central control.
- You can select FCS-6326-43 (with lifting touch screen) for upgrading to a multimedia meeting room.
- Completely avoid the interference of electromagnetic wave from 3G/4G cell phone even within 10cm distance.
- Equipped with shield and flexible gooseneck tube, which is easy to be positioned. Even bending it normally, it would not make any noise.

## Connection

**Each lifting microphone box should connect with the standard control box to operate speaking control, RS-485 control, and parallel connection. We offer RJ cables to enhance the convenience and simplicity of cabling.**




BXB Electronics Co., Ltd.
A：6F-1, No.288-5, Xinya Rd., Qianzhen Dist., Kaohsiung City 80673, Taiwan
T：+ 886 7 9703838
F：+ 886 7 9703883
E：b x b @ b x b . t w
w w w . b x b . t w

## Applications




### Hardware Specifications

| | |
|---|---|
| Panel Buttons | Speaking x 1; lifting / stop / descending x 1 |
| Control Ports | RS-485/RS-232 |
| Lifting Time | 310mm/10s |
| Frequency Response | 65~20000Hz |
| Input Impedance | 1Khz; 680Ω |
| Sensitivity | -47±3dB (0dB=1V/Pa,at 1KHz) |
| Max. SPL | THD<5%, at 1KHz |
| S/N Ratio | S: F=1KHz,S.P.L=1Pa N: A-Weighted curve |
| Directivity | Cardioid |

### Physical Properties

| | |
|---|---|
| Panel Dimensions (WxHxD) | 113 x 73mm |
| Material | Aluminum alloy |
| Mounting Size | 106.5 x 65mm |
| Box Size | 113 x 73 x 690mm |
| Net Weight | 5.5Kg |
| Microphone Length | Standard 32/43cm |

### Power Supply

| | |
|---|---|
| Voltage | AC 220V/60Hz@50Hz |
| Power Consumption | 15W |

BXB Electronics Co., Ltd.
A：6F-1, No.288-5, Xinya Rd., Qianzhen Dist., Kaohsiung City 80673, Taiwan
T：+ 886 7 9703838 F：+ 886 7 9703883
E：b x b @ b x b . t w
w w w . b x b . t w