FCS-6315 / 6316

Table-top Chairman/Delegate Unit



TAIWAN EXCELLENCE 2015

- With built-in voting interface with five buttons in the lid. It can operate with BXB's graphical control software to do voting function.
- Equipped with built-in 2.5" x 1.5" HI FI speaker. When the microphone is on, the loudspeaker would be auto-off to avoid sound feedback.
- Equipped with DSP chip: sensitivity adjustment for each microphone.
- Equipped with 2 x 24 digit LCD display to show operation modes and speaking statuses.
- Equipped with digital coding. Each unit's ID number and the identity of chairman/delegate can be set by main control unit or graphical software directly.
- Equipped with Ø3.5mm plug x 2 for connecting recording equipment and earphone.
- Available length of pluggable gooseneck microphone: 32/43/48/56 (cm). Adaptable with different meeting environments.

Specifications

Connector	RJ45 x 1
Earphone Port	3.5Ø Stereo x 1
Recording Port	3.5Ø Stereo x 1
Frequency Response	100Hz~16KHz
T.H.D	≦ 0.5%

S/N Ratio	58dB
Sensitivity	-47±3dB
Dimensions (WHD)	170 x 50 x 132mm
Weight	877g (not including gooseneck mic)

Top Material	ABS
Base Material	Zinc-aluminum alloy diecast & anti-slip mat
Voltage	DC 12~24V (supplied by FCS - 6350 MCU)

BXB
ADD 6F-1, No.288-5, Xinya Rd., Qianzhen Dist., Kaohsiung City 806604, Taiwan
TEL +886 7 9703838
FAX +886 7 9703883
MAIL bxb@bxb.tw
WEB www.bxbsystem.com