ICP-5132

HDMI Network Signal Converter





- Operate with BXB ICP-5180 Central Control Unit to execute A/V matrix broadcasting.
- Connect with DVD players, cameras, PCs, and other A/V equipment for live-streaming.
- Equipped with HDMI 1.3b input connector for IP streaming with 1080p video quality.
- Resolution supported: 480i/p, 576i/p, 720p, 1080i/p
- Extensible for 8 converters for playing 8-CH multimedia files.
- Supports S/PDIF and analog stereo audio outputs for audio monitoring.
- HDCP compatible for digital copy protection.
- Local firmware upgrade via the USB 2.0 connector.

Product Specifications

Interfaces	HDMI IN x 1; HDMI OUT x 1; Ethernet: RJ45 female; 3.5mm Stereo Jack x 1 ; S/PDIF port x 1 ; USB 2.0 x 1
Protocols	IP, TCP, UDP, RTP, RTCP, IPv4, DHCP, HTTP, IGMP, ICMP, MULTICAST, UNICAST
Streaming Media Formats	H.264 baseline profile level 1.0 to 4.0; up to 1080 30p/15Mbps video and 48K/16bit 192K MP3 audio
Video Formats	1080p 50/60, 1080i 50/60, 1080p 25/30, 720p 50/60, 480p 50/60,
LED Indicator	Standby x 1 (red)
Dimensions (WHD)	238 x 26 x 97mm
Weight	460g
Power Consumption	Standby Current: 1.62mA @ DC 5V

BXB
ADD 6F-1, No.288-5, Xinya Rd., Qianzhen Dist., Kaohsiung City 80673, Taiwan
TEL +886 7 9703838
FAX +886 7 9703883
MAIL bxb@bxb.tw
WEB www.bxbsystem.com