BXB-CCU3
Central Control Unit



- High-performance CPU: easily meet the demands of conference room management and broadcasting system control via BXB graphical control software.
- Lightweight and compact, which can be stored in BXB 6U cabinets.
- USB KEY activation mechanism: allows for fast installation even in internet environment, while ensuring the security of product licensing.
- Built-in dual network cards: simultaneously operates with LAN and external network; convenient and efficient.
- Built-in service mechanism: in case of system's abnormal conditions, the built-in program can transmit service information to BXB headquarter via the network.

Product Specs

OS	Windows 10 Iot Ent LTSC
Processor	Intel® Celeron® J3455 1.50GHz (Max. 2.3GHZ), 4 cores
Memory	DDR3, 800.0 MHz x 2, 8GB
Storage	512GB
Front I/O Ports	USB 3.0 x 2 LINE out x 1 MIC in x 1
Rear I/O Ports	DIN-9 RS-232 x 1 USB 2.0 x 1, USB 3.0 x 1 RJ-45 TCP/IP x 2 HDMI 1.4 x 1 Displayport x 1 Power port x 1

Dimensions (HWD)	20 x 200 x 137.8 mm
Weight	0.9Kg (without transformer)
Operating Temperature	0°~50°C
External Power Supply Voltage	DC 12V 3A MAX
Voltage/Frequency	110/220V
Power of Standard Transformer	36W
In the Box	CCU3 Central Control Unit x 1 USB KEY x 1 Keyboard & mouse x 1 Activation manual x 1

BXB
ADD 6F-1, No.288-5, Xinya Rd., Qianzhen Dist., Kaohsiung City 806604, Taiwan
TEL +886 7 9703838
FAX +886 7 9703883
MAIL bxb@bxb.tw
WEB www.bxbsystem.com