www.bxb.tw

Your Best Partner!
with Ultimate Choice!!

PA-5120P2 Mixing Amplifier



TECHNICAL SPECIFICATION		
Voltage	AC 110V/60Hz 220V/50Hz DC 24V	
Frequency Response	Aux 74Hz - 19KHz Mic 77Hz - 19KHz	
Input Terminal Sensitivity	Aux -30 dB Mic -64 dB	
Tone Control	Music	Bass 100Hz -12 dB - +12 dB Treble 10Hz -13 dB - +11 dB
	Mic	Bass 100Hz -12 dB - +12 dB Treble 10Hz -13 dB - +11 dB
Signal to Noise Ratio	Aux -85dB Mix -85dB	
Total Harmonic Distortion(THD)	< 0.6 %	
Total Power Loading	495 W	
Power Output	240W/ RMS	
Power Indicator	LED Display	
Dimension (mm)	420W X 379 DX 96H mm	
Weight	13 kg	

*Appearance and specifications of all items may subject to change without notice

6F.-1, No.288-5, Xinya Rd., Qianzhen Dist., Kaohsiung City 806, Taiwan (R.O.C.)
TEL：+886(7)970-3838 FAX：+886(7) 970-3883 Email: bxb@bxb.tw http://www.bxb.tw
BXB ELECTRONICS CO., LTD. All rights reserved.