VDM-4024

Distributed AV over IP Switch



Product Features

- Designed for medium network environments as enterprises to strengthen the long-distance AV signal/video stream transmission.
- 24 sets of 10/100/1000 Mbps Ethernet ports with 2 optical port SFP.
- Able to identify the corresponding network ports that interconnect with the receivers and transmiters.
- Intuitive Web UI interface for system configurations, supporting Traditional Chinese, Simpliied Chinese, Russian, and English.
- Monitors the images of transmitters and receivers instantly with ease.
- Easy scanning of all devices in the system.
- Supports RTSP port, IGMP snooping, and SNMP.
- Supports LLDP for checking other connected devices in the system.
- Login authorization control with an individual password.
- Backplane bandwidth: 56Gbps.
- Equipped with a RS-232 connector.

Specifications

Interface & System Performance

10 / 100 / 1000 Base-T RJ45	24 ports
10G SFP+Slot	2 ports
CLI Management	1 port
RS-232	1 port
Backplane bandwidth	56Gbps

Layer 2 Features

Flow Control (duplex)	802.3x full & half
IGMP Snooping	IGMP snooping v1/v2/v3: supports 1024 IGMP groups & 1024 static multicast addresses
Storm Control	Broadcast/Multi-cast/Un-known Unicast
Jumbo Frame Support	9.6KB

Other Technical Specifications

Management	User name/password protection Command line (CLI), web-based, Telnet interface Firmware upgrade via SNMP/WEB/SSH/TELNET Configuration download/upload; SNMP (v1/v2c/v3)

Physical Properties

Dimensions (WHD)	440 x 285 x 44 mm
Weight	3.31 KG
Operating Temperature	0 ~ 50°C
Storage Temperature	-20 ~ 80°C
Relative Humidity	10 ~ 90% (non-condensing)

Power Supply

Internal Power Supply	AC 100-240V, 50-60Hz
Power Consumption	< 60 Watt

BXB
ADD 6F-1, No.288-5, Xinya Rd., Qianzhen Dist., Kaohsiung City 80673, Taiwan
TEL +886 7 9703838
FAX +886 7 9703883
MAIL bxb@bxb.tw
WEB www.bxbsystem.com